



Monitoring & Maintenance Engineering, Inc.

PHOSter Case History

Bullard Property

SCDHEC Site #17477

St. Stephen, South Carolina

Project Management

The management team for this project included Read Miner at South Carolina Department of Health and Environmental Control and Rick Smith of Smith Monitoring and Maintenance Engineering, Inc.

Site Description:

This site is located in the Outer Coastal Plain of South Carolina near Lake Moultrie. The site was previously a filling station prior to the expansion of the adjacent US highway to four lanes, leaving slight contamination of predominately benzene and naphthalene below the pavement and on either side of the highway. Soils are sandy silt to approximately eight feet below grade, turning to silty-clay and then kaolin to twelve feet. Below the kaolin is sand to more than 30'. The neighboring church and residences used private wells as their primary drinking water source.

PHOSter System

Due to the shallow groundwater, slight contaminant concentrations and sandy residuum soils, this application was designed using a 49' radius of influence (ROI). A two-injector skid-mounted system was used for bio-sparging and nutrient injection. These systems use less than 500 kWh per month of power.

Start-up

The PHOSter system was mobilized to the site, connected to the electrical service and the site piping in May 1999. Since the system and injection wells were located in minimal traffic areas, this installation used 3/8" pressure hose anchored to soil between the system and the injection wells. Time required for skid set-up, electrical connection, and in-well diffuser installation was approximately four hours.

Remediation Progress

Remediation on the west side of the highway was confirmed complete after eight months of operation. The system remained in operation, at injection wells MW-1 and MW-4, for an additional nine months until results showed contaminants of concern below target levels on the east side of the highway (MW-2 and MW-8). Of the primary biologically important components, oxygen will remain dissolved in water until it is used or reacts with soil minerals (easily overcome with constant low-rate air sparge), the phosphate compound is 100 percent miscible in water and while it can bind with certain metals, can usually be assumed to have a 100' or better ROI (we have measured phosphate ROI greater than 200 feet). In this case, the hottest well on this site was remediated by injection wells at a distance of 125 feet.

145 Merrill Avenue; Decatur, Georgia 30030


Phone: 404 371-9332 Cell: 404 229-3096

e-mail: ricksme@gmail.com


Website: www.bioremediationsmme.com


FIGURES

MW-2 Concentrations of Concern



MW-8 Concentrations of Concern





South Carolina DHEC
2600 Bull Street
Columbia, South Carolina

SMME Smith Monitoring & Maintenance Engineering, Inc.
Engineering, Wastewater and Groundwater Remediation System Consultation, Operation and Maintenance
145 Merrill Avenue Decatur, Georgia 30030
Telephone: (404) 371-9332

PROJECT #:

DRAWN BY: RBS

SCALE: 1" = 50'

DATE: April 1999

Pre-Remediation Plan
Benzene/Naphthalene Isoleth Map
Bullard Property
St. Stephen, South Carolina

FIGURE
1